



3 PRO



dB-3Pro™ is a mass loaded, limp vinyl sound damping material designed for commercial, industrial, and residential applications to reduce sound transmission. It is used primarily behind finished wall or ceiling surfaces to block and damp noise through the entire sound spectrum.

Specifications

Weight: 1.0 lb./ft² nominal

Tolerances:

- Width: +0.5" / - 0"
Length: + 1.0% / -0%

Specifications:

- 4' x 8' sheet size
4' x 10' sheet size
4' x 25 roll size

Performance

- Approved in UL wall assemblies U300, U400, & V400 (Report: CLB.V.R38761)
Flammability rating of class 1 per ASTM E 84 Rev A, behind a minimum of 3/8" gypsum
No fungal or algae growth or visible disfigurement per ASTM D3273 and ASTM G21
Meets 1 hour fire resistance rating per ASTM E119

Table with 9 columns: Assembly Description, STC, 125 Hz, 250 Hz, 500 Hz, 1,000 Hz, 2,000 Hz, 4,000 Hz, Test Number. Rows include Baseline (16" O.C. 2" x 4" Wood Studs) and Test Condition (16" O.C. 2" x 4" Wood Studs with dB-3 Pro™).

Table with 9 columns: Assembly Description, STC, 125 Hz, 250 Hz, 500 Hz, 1,000 Hz, 2,000 Hz, 4,000 Hz, Test Number. Rows include Baseline (16" O.C. 3 5/8" Metal Studs) and Test Conditions 1 and 2.

About Us:

Located in Mount Airy, North Carolina, United Plastics Corporation has been producing quality plastic products since 1946. Our soundproofing materials are used in multi-family housing, hotels, commercial properties, and residential properties throughout the United States.



511 Hay Street | PO Box 807 | Mount Airy, North Carolina 27030
336.786.2127 | info@dBSoundControl.com | www.dBSoundControl.com