



4 PRO



dB-4Pro™ is a mass loaded, limp vinyl sound damping material designed for commercial, industrial, and residential applications to reduce sound transmission. It is used primarily underneath hard surfaces to reduce both impact and airborne noises.

Specifications

Weight: 0.9 lb./ft² nominal

Tolerances:

- Width: +0.5" / - 0"
Length: + 1.0% / -0%

Specifications:

- 3' x 34' roll size

Performance

- Approved in all UL floor-ceiling assemblies of the L500 series (Report: CLBV.R38761)
Flammability rating of class 1 per ASTM E 84 Rev A, under a class 1 flooring surface
No fungal or algae growth or visible disfigurement per ASTM D3273 and ASTM G21
Meets 1 hour fire resistance rating per ASTM E119

Table with 9 columns: Assembly Description, IIC, 80 Hz, 100 Hz, 125 Hz, 250 Hz, 500 Hz, 1,000 Hz, Test Number. Rows include Baseline, Test Condition 1, and Test Condition 2 for various floor/ceiling assemblies.

Table with 9 columns: Assembly Description, IIC, 80 Hz, 100 Hz, 125 Hz, 250 Hz, 500 Hz, 1,000 Hz, Test Number. Rows include Baseline, Test Condition 1, and Test Condition 2 for concrete floor assemblies.

About Us:

Located in Mount Airy, North Carolina, United Plastics Corporation has been producing quality plastic products since 1946. Our soundproofing materials are used in multi-family housing, hotels, commercial properties, and residential properties throughout the United States.



511 Hay Street | PO Box 807 | Mount Airy, North Carolina 27030
336.786.2127 | info@dBSoundControl.com | www.dBSoundControl.com